

## LD/C

### ES

**Montaje:** Empotrable.

**Fuente de luz:** Módulos lineales LED SMD.  
Temperatura de color 4000K.  
Disponible, 3000K, 6000K.

**Sistema óptico:** Difusor.

**Distribución luminosa:** Indirecta.

**Equipo eléctrico:** Equipo de control electrónico. PF>0,95.  
Disponible, regulable DALI y/o kit de emergencia (1-3 h).

**Materiales:** Cuerpo: Acero de alta resistencia a la torsión y espesores mínimos garantizados de 0,6mm, según Normas ENEC-10 y VDE. Difusor: Microperforado. Rápida accesibilidad a la borna de conexión.

**Acabado:** Cuerpo: Epoxi-poliéster en blanco opaco y satinado anti-reflejos y antideslumbramiento.



### EN

**Mounting:** Recessed.

**Light source:** LED linear modules SMD.  
Temperature color 4000K.  
Available, 3000K, 6000K.

**Optical system:** Diffuser.

**Light distribution:** indirect.



**Electrical equipment:** Electronic control gear. PF>0,95.  
Available, dimmable DALI and/or emergency kit (1-3 h).

**Materials:** Body: High resistance steel with guaranteed minimum thickness of 0.6mm, according to ENEC-10 and VDE standards. Diffuser: Microperforated. quick accessibility to the connection terminal.

**Surface finish:** Body: Epoxy-polyester in white opaque and satin antiglare.




LD/C-32W




FLICKER FREE


MICROPERFORADO  
MICROPERFORATE



#### ESTANDAR/STANDARD



#### DISPONIBLE/AVAILABLE



#### CONFIGURACION ONLINE ONLINE CONFIGURATION



| Código<br>Code | Referencia<br>Reference | Kg<br>Kg | Potencia<br>Power | Lúmenes<br>Lumens | Eficiencia<br>Efficiency | CCT (K)<br>CCT (K) |
|----------------|-------------------------|----------|-------------------|-------------------|--------------------------|--------------------|
| LDC223K2B      | LD/C-25W 3800lm/840     | 5,0      | 25W               | 3800              | 152 lm/W                 | 4000               |
| LDC224K4B      | LD/C-32W 4800lm/840     | 5,0      | 32W               | 4800              | 150 lm/W                 | 4000               |

#### ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING DALI    KIT DE EMERGENCIA/EMERGENCY KIT 1h | 3h    T.COLOR 3000K, 6000K    ACCESORIO PARA ADOSAR/ACCESSORY FOR SURFACE