

PSB/MCR-UGR<18 600x600 mm

ES

Montaje: Adosable.

Fuente de luz: Módulos lineales LED SMD.
Tunable white: 2700K - 6500K.

Sistema óptico: Difusor microprismático.

Distribución luminosa: Directa.

Equipo eléctrico: Equipo de control electrónico. PF>0,95. Control de intensidad luminica y temperatura de color (DIMM DALI DT8).

Materiales: Cuerpo: Acero de alta resistencia a la torsión, según Normas ENEC-10 y VDE. Marco de la luminaria: Aluminio extruido lacado en blanco de diseño profesional. Difusor: Microprismático.

Acabado: Color blanco RAL 9003.



EN

Mounting: Surface.

Light source: LED linear modules SMD.
Tunable white: 2700K - 6500K.

Optical system: Microprismatic diffuser.

Light distribution: Direct.


Electrical equipment: Electronic control gear. PF>0,95. Luminous intensity and colour temperature control (DIMM DALI DT8).

Materials: Body: High resistance steel with, according to ENEC-10 and VDE standards. Diffuser: Microprismatic.

Surface finish: White color RAL 9003.



PSB/MCR-UGR<18-38W



DALI



REGULADOR DE LUZ NATURAL Y SENSOR DE PRESENCIA
NATURAL LIGHT DIMMING AND PRESENCE SENSOR



DISPONIBLE/ AVAILABLE

Controlador de temperatura de color y potencia.
Temperature color and power controller.



ESTANDAR/STANDARD
TUNABLE WHITE



CONTROL DE INTENSIDAD LUMINICA Y TEMPERATURA DE COLOR/
LUMINOUS INTENSITY AND COLOUR TEMPERATURE CONTROL
(DIMM DALI DT8)

PSB/MCR-UGR<18+KIT ADOSAR



ESTANDAR/STANDARD

5 AÑOS 5 YEARS	220-240V 50-60Hz	IP 20	IK 02	CLASE I CLASS I	50.000h L80B10	-20° +40°	CRI 80	DALI	TUNABLE WHITE 2700-6500K

CONFIGURACION ONLINE
ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT (K)
PMC224KWBN	PSB/MCR-UGR<18-38W 4500lm/TW 827-865+ACC. KIT ADOSAR/SURFACE	2,5	38W	4500	118 lm/W	2700 - 6500
PMCCTW	CONTROLADOR PSB/MCR TW	-	-	-	-	-

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING 1-10V | DALI CONTROLADOR PSB/MCR TW SET DE SUSPENSION/SUSPENSION SET
REGULADOR DE LUZ + DETECTOR DE PRESENCIA (RLP)/AMBIENT LIGHT + PRESENCE SENSOR (RLP)

