

TPB/OPAL 600x600 mm


ES

Montaje: Empotrable.
Fuente de luz: Módulos lineales LED SMD.
 Temperatura de color 4000K.
 Disponible, 3000K, 6000K.
Sistema óptico: Difusor opal.
Distribución luminosa: Directa.
Equipo eléctrico: Equipo de control electrónico. PF>0,95.
 Disponible, regulable 1-10V o DALI y/o kit emergencia (1-3 h).
Materiales: Cuerpo: Acero de alta resistencia a la torsión. Marco de la luminaria: Aluminio extruido lacado en blanco de diseño profesional. Difusor: Opal.
Acabado: Color blanco RAL9003.



EN

Mounting: Recessed.
Light source: LED linear modules SMD.
 Temperature color 4000K.
 Available, 3000K, 6000K.
Optical system: Opal diffuser.
Light distribution: Direct.
Electrical equipment: Electronic control gear. PF>0,95.
 Available, dimmable 1-10V or DALI and/or emergency kit (1-3 h).
Materials: Body: High resistance steel. Frame: Professional design of extruded aluminum lacquered in white. Diffuser: Opal.
Surface finish: White color RAL 9003.



FLICKER FREE




<19

Disponible/Available + info p. 95

SENSOR DE LUZ Y PRESENCIA Y REGULACION DE LUZ AMBIENTE INTEGRADO EN LA LUMINARIA
LIGHT AND PRESENCE SENSOR AND AMBIENT LIGHT DIMMING INTEGRATED ON THE LUMINAIRE

<p>DALI</p>	<p>1-10V</p>	<p>MARCO PARA EMPOTRAR ACCESSORY FOR RECESS</p>	<p>GARRAS PARA TECHOS CLIP IN BRACKETS FOR RECESS</p>	<p>ACCESORIO PARA ADOSAR ACCESSORY FOR SURFACE</p>
-------------	--------------	---	---	--



ESTANDAR/STANDARD

5 AÑOS 5 YEARS	220-240V 50-60Hz	IP 40	IK 02	CLASE I CLASS I	50.000h L80B10	-20° +40°	CRI 80
-------------------	---------------------	-------	-------	--------------------	-------------------	--------------	--------

DISPONIBLE/AVAILABLE

1-10V DALI	3000K 6000K	EMERGENCY 1h 3h
---------------	----------------	-----------------------

CONFIGURACION ONLINE ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT(K) CCT(K)
TPO224K4B	TPB/OPAL-32W 4400Lm/840 PH	1,3	32W	4400	137 lm/W	4000
TPO225KLB	TPB/OPAL-40W 5250Lm/840 LM	1,3	40W	5250	131 lm/W	4000
TPO2252LB	TPB/OPAL-40W 5250Lm/840 PH/TR	1,3	40W	5250	131 lm/W	4000
TPO2252EB	TPB/OPAL-40W 5250Lm/840 TR EU	1,3	40W	5250	131 lm/W	4000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING 1-10V DALI	KIT DE EMERGENCIA/EMERGENCY KIT 1h 3h	T.COLOR 3000K, 6000K	ACCESORIO PARA EMPOTRAR/ACCESSORY FOR RECESS
ACCESORIO PARA ADOSAR/ACCESSORY FOR SURFACE	KIT PARA ADOSAR/KIT FOR SURFACE	SET DE SUSPENSION/SUSPENSION SET	
MUELLES PARA TECHO DE ESCAYOLA/PLASTER CEILING SPRINGS	GARRAS PARA TECHO CLIP-IN, TECHO OCULTO.../BRACKETS FOR CLIP-IN CEILING, HIDDEN CEILING...		
REGULADOR DE LUZ + DETECTOR DE PRESENCIA (RLP)/AMBIENT LIGHT + PRESENCE SENSOR (RLP)	RLP (1-10V) INTEGRADO/INTEGRATED	DETECTOR DE PRESENCIA (SLP)/PRESENCE DETECTOR (SLP)	

