

ASTRO-IP65

ES

Montaje: Empotrable.

Fuente de luz: Módulos compactos LED COB VOSSLÖH.
Temperatura de color 4000K.
Disponible, 3000K, 5000K.

Sistema óptico: Reflector aluminio brillante facetado. Cristal transparente (modelo estándar ASTRO/TR). Disponible, cristal opal (modelo ASTRO/OPAL).

Distribución luminosa: Directa.

Equipo eléctrico: Equipo de control electrónico. PF>0,95. Disponible, regulación 1-10V o DALI y/o kit de emergencia (1-3h).

Materiales: Cuerpo: Aluminio extruido lacado en blanco. Reflector: Aluminio brillante. Difusor: Cristal templado.

Acabado: Color blanco RAL 9003.



EN

Mounting: Recessed.

Light source: LED compact modules COB VOSSLÖH.
Temperature color 4000K.
Available, 3000K, 5000K.

Optical system: Faceted bright aluminium reflector. Transparent glass (ASTRO/TR standard model). Available, opal glass (ASTRO/OPAL model).

Light distribution: Direct.

Electrical equipment: Electronic control gear. PF>0,95. Available, dimmable electronic control gear 1-10V or DALI and/or emergency kit (1-3h).

Materials: Body: Aluminum extruded lacquered in white. Reflector: Bright aluminium. Diffuser: Tempered glass.



Surface finish: White RAL 9003.



ESTANDAR | STANDARD



ASTRO/TR-IP65-145-25W

ASTRO/TR-IP65-196-25W




ASTRO/TR-IP65-242-52W

ASTRO/OPAL-IP65-242-52W




IP-65


SALAS BLANCAS
CLEAN ROOM



ASTRO-145



ASTRO-196



ASTRO-242

ESTANDAR/STANDARD



5 AÑOS
5 YEARS



220-240V
50-60Hz



IP 65



IK 07



CLASE I
CLASS I



50.000h
L80B10



-20°
+35°



CRI 80



1-10V
DALI



3000K
5000K



1h
3h

CONFIGURACION ONLINE
ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT (K) CCT (K)
AST1P1K6B	ASTRO/TR-IP65-145 12W 1600lm/840	0,4	12W	1600	133 lm/W	4000
AST1P1KEB	ASTRO/TR-IP65-145 12W 1600lm/840 TR/EU	0,4	12W	1600	133 lm/W	4000
AST1P2KEB	ASTRO/TR-IP65-145 18W 2200lm/840 TR/EU	0,4	18W	2200	122 lm/W	4000
AST1P3KEB	ASTRO/TR-IP65-145 25W 3000lm/840 TR/EU	0,4	25W	3000	120 lm/W	4000
AST2P2K3B	ASTRO/TR-IP65-196 18W 2300lm/840	0,8	18W	2300	128 lm/W	4000
AST2P2KEB	ASTRO/TR-IP65-196 18W 2300lm/840 TR EU	0,8	18W	2300	128 lm/W	4000
AST2P3KEB	ASTRO/TR-IP65-196 25W 3200lm/840 TR EU	0,8	25W	3200	128 lm/W	4000
AST3P3K2B	ASTRO/TR-IP65-242 25W 3200lm/840	1,0	25W	3200	128 lm/W	4000
AST3P3KEB	ASTRO/TR-IP65-242 25W 3200lm/840 TR EU	1,0	25W	3200	128 lm/W	4000
AST3P4KEB	ASTRO/TR-IP65-242 37W 4500lm/840 TR EU	1,0	37W	4500	122 lm/W	4000
AST3P5KEB	ASTRO/TR-IP65-242 52W 5700lm/840 TR EU	1,0	52W	5700	110 lm/W	4000

ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMMING 1-10V | DALI KIT DE EMERGENCIA/EMERGENCY KIT 1h | 3h T.COLOR 3000K, 5000K SUJECION PARA TECHO DE ESCAYOLA/FORCE FOR PLASTER CEILIN
REGULADOR DE LUZ + DETECTOR DE PRESENCIA (RLP)/AMBIENT LIGHT + PRESENCE SENSOR (RLP) DETECTOR DE PRESENCIA (SLP)/ PRESENCE DETECTOR (SLP)
DIFUSOR OPAL/DIFFUSER OPAL

