

## ZIPL0-75

### ES



**Montaje:** Integrado en carril.

**Fuente de luz:** Módulos compactos LED COB TRIDONIC. Temperatura de color 4000K. Disponible, 2700K, 3000K.

**Sistema óptico:** Reflector.

**Distribución luminosa:** Directa. Óptica estándar de 24°. Disponibles ópticas de 16°, 38°.

**Equipo eléctrico:** Equipo de control electrónico TRIDONIC. PF>0,95. Disponible, regulable DALI.

**Materiales:** Cuerpo: Aluminio lacado al horno y texturizado. Difusor: Transparente con moteado perimetral. Reflector: Aluminio facetado.

**Acabado:** Color blanco RAL 9003 (estándar). Disponible, negro RAL 9005. Otros colores bajo consulta.

### EN



**Mounting:** Integrated in track.

**Light source:** LED compact modules COB TRIDONIC. Temperature color 4000K. Available, 2700K, 3000K.

**Optical system:** Reflector.


**Light distribution:** Direct. Standard lens 24°. Available lenses of 16°, 38°.

**Electrical equipment:** TRIDONIC electronic control gear. PF>0,95. Available dimmable DALI.


**Materials:** Body: Baked lacquered and textured aluminium. Diffuser: Transparent with perimeter mottling. Reflector: Faceted aluminium.

**Surface finish:** White color RAL 9003 (standard). Available, black RAL 9005. Other colors under request.


ESTANDAR | STANDARD  
ZIPL0-75-24°-26W




ZIPL0-75-16°-26W




ZIPL0-75-38°-26W



ESTANDAR COLOR BLANCO  
STANDARD WHITE COLOR



#### ESTANDAR/STANDARD



#### DISPONIBLE/AVAILABLE



#### CONFIGURACION ONLINE ONLINE CONFIGURATION



Código Code	Referencia Reference	Kg Kg	Potencia Power	Lúmenes Lumens	Eficiencia Efficiency	CCT (K) CCT (K)
ZIP113K0B	ZIPL0-75-24°-19W 3040lm/840	0,6	19W	3040	160 lm/W	4000
ZIP114K0B	ZIPL0-75-24°-26W 4160lm/840	0,8	26W	4160	160 lm/W	4000













#### ACCESORIOS DISPONIBLES/AVAILABLE ACCESSORIES

REGULACION/DIMING DALI T.COLOR 2700K, 3000K OPTICA/LENS 16°, 38°

BAJO CONSULTA/UNDER REQUEST CRI>90

**ACCESORIOS | ACCESSORIES**

DE CARRIL TRIFÁSICO DE 3 O 5 POLOS/THREE-PHASE TRACK 3 OR 5 PINES

<b>CARRIL EMPOTRADO RECESSED TRACK</b>	<b>CODIGO/CODE 3 POLOS/ 3 PINES</b>	<b>CODIGO/CODE 5 POLOS/ 5 PINES</b>	<b>CARRIL ADOSADO SURFACE TRACK</b>	<b>CODIGO/CODE 3 POLOS/ 3 PINES</b>	<b>CODIGO/CODE 5 POLOS/ 5 PINES</b>
	<b><u>ZIPCE23PB</u></b> Carril empotrado Recessed electrified track 2 m	<b><u>ZIPCE25PB</u></b> Carril empotrado Recessed electrified track 2 m		<b><u>ZIPCS23PB</u></b> Carril adosado Surface electrified track 2 m	<b><u>ZIPCS25PB</u></b> Carril empotrado Surface electrified track 2 m
	<b><u>ZIPCE33PB</u></b> Carril empotrado Recessed electrified track 3 m	<b><u>ZIPCE35PB</u></b> Carril empotrado Recessed electrified track 3 m		<b><u>ZIPCS33PB</u></b> Carril adosado Surface electrified track 3 m	<b><u>ZIPCS35PB</u></b> Carril empotrado Surface electrified track 3 m
	DERECHO/ RIGHT <b><u>ZIPAD3PB</u></b> IZQUIERDO/LEFT <b><u>ZIPAI3PB</u></b> Alimentador final derecho/izquierdo Final connection right/left	DERECHO/ RIGHT <b><u>ZIPAD5PB</u></b> IZQUIERDO/LEFT <b><u>ZIPAI5PB</u></b> Alimentador final derecho/izquierdo Final connection right/left		<b><u>ZIPUC3PB</u></b> Unión interna carril Track internal joint	<b><u>ZIPUC5PB</u></b> Unión interna carril Track internal joint
	<b><u>ZIPUL3PB</u></b> Unión en "L" carril "L" track joint	<b><u>ZIPUL5PB</u></b> Unión en "L" carril "L" track joint		<b><u>ZIPUT3PB</u></b> Unión en "T" carril "T" track joint	<b><u>ZIPUT5PB</u></b> Unión en "T" carril "T" track joint
	<b><u>ZIPUX3PB</u></b> Unión en "X" carril "X" track joint	<b><u>ZIPUX5PB</u></b> Unión en "X" carril "X" track joint		<b><u>ZIPUF3PB</u></b> Pieza unión codo flexible carril Flexible track joint	<b><u>ZIPUF5PB</u></b> Pieza unión codo flexible carril Flexible track joint
	<b><u>ZIPSUSB</u></b> Set de suspensión Suspension set			<b><u>ZIPTFB</u></b> Tapa final Last cover	

